




# Rim and Tyre Specifications

---

Bawa Trailer Parts

*Version 1.0*

 07 3277 5349

 [bawatrailerparts@gmail.com](mailto:bawatrailerparts@gmail.com)

 [bawatrailerparts.net.au](http://bawatrailerparts.net.au)



## How to use this document:

The best way to make use of this document is firstly recognising whether you are after rims only, tyres only or rim and tyre assemblies. Once you have recognised this, please check our website for the wheel you are after and then find the code listed. *(Please see an example of where that will be in the image below)*. Once you have found the code, use the contents list below to find which page will have what you're after and then look for your specific code!

### RIM AND TYRE SPECIFICATIONS:

RIM + TYRE	Tyre Size	Backspace	Frontspace	Offset	Single Rating	Double Rating
WRTFHT13P155	155	80mm	80mm	0	515kg	487kg
WRTFHT13P165	165	85mm	77mm		670kg	650kg
WRTFHT13P175	175	90mm	80mm		730kg	690kg
WRTF13G195	195/50	105mm	95mm		900kg	825kg
WRTF14P (+)	185/	110mm	75mm	+14	850kg	800kg
WRTF14P (0)	185	100mm	100mm	0	850kg	800kg
WRTF14P195	195	120mm	85mm	+	950kg	900kg
WRTL14P	185	100mm	100mm	0	850kg	800kg
WRTL14P195	195	105mm	105mm	0	950kg	900kg
WRTHQ14P	185	110mm	75mm	+	850kg	800kg
WRTHQ14P195	195	115mm	80mm	+	950kg	900kg
WRHT14P	185	110mm	75mm	+	850kg	800kg
WRHT14P195	195	115mm	80mm	+	950kg	900kg
WRTMF14G	185	105mm	105mm	0	850kg	800kg
WRTMF14G195	195	105mm	105mm	0	950kg	900kg
WRTHQ14G	185	110mm	75mm	+	850kg	800kg

## Contents:

*Page 3 – Rim Specifications*

*Page 4 – Tyre Specifications*

*Page 5 – Rim and Tyre Specifications*



## RIM SPECIFICATIONS:

<b>RIM</b>	<b>SIZE</b>	<b>Stud Pattern</b>	<b>Offset</b>	<b>PCD</b>	<b>Centre Bore</b>	<b>Load Rating</b>
<b>WRHT/F13P</b>	13x4.5	Ford/HT Multifit	0	5 x 114.3 /5 x 108	75	650kg
<b>WRHT/F13G</b>	13x4.5	Ford/HT Multifit	0	5 x 114.3 /5 x 108	75	650kg
<b>WRF13G</b>	13x6	Ford	5	5 x 114.3	83.7	850kg
<b>WRF14P</b>	14x6	Ford	+14	5 x 114.3	83.7	850kg
<b>WRF14G</b>	14x6	Ford	+14	5 x 114.3	83.7	850kg
<b>WRHQ14P</b>	14x6	HQ	+14	5 x 120.65	83.7	850kg
<b>WRHT14P</b>	14x6	HT	+14	5 x 108	83.7	850kg
<b>WRLC14P</b>	14x6	6 Stud LC	+14	6 x 139.7	108.7	850kg
<b>WRLC15P</b>	15x6 OR 15x7	6 Stud LC	0	6 x 139.7	108.7	1050kg
<b>WRLC15G</b>	15x7	6 Stud LC	0	6 x 139.7	108.7	1250kg
<b>WRLC15PB</b>	15x7	6 Stud LC	0	6 x 139.7	108.7	1250kg
<b>WRF15P</b>	15x7	Ford	0	5 x 114.3	83.7	1250kg
<b>WRLC16P</b>	16x7	6 Stud LC	0	6 x 139.7	108.7	1480kg
<b>WRLC16PB</b>	16x7	6 Stud LC	0	6 x 139.7	108.7	1480kg



## TYRE SPECIFICATIONS:

<b>TYRE</b>	<b>WIDT H</b>	<b>_/_ (_PR)</b>	<b>TREAD*</b>	<b>SIDEWALL</b>	<b>Load Rating</b>
<b>TLT13R155C</b>	155mm	85/83N (6PR)	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	650kg
<b>TLT13R165C</b>	165mm	94/93N (8PR)	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	670kg
<b>TLT13R175C</b>	175mm	97/95Q (8PR)	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	730kg
<b>TLT13R195C</b>	195mm	104/101N (8PR)	8 PLIES	2 PLIES POLYESTER	900kg
<b>TLT14R185C</b>	185mm	102/100R (8PR)	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	850kg
<b>TLT14R195C</b>	195mm	106/104S (8PR)	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	950kg
<b>TLT15R195C</b>	195mm	-	4 PLIES (2 P + 2 S)	2 PLIES POLYESTER	950kg
<b>TLT15R225C</b>	225mm	-	5 PLIES (2 P + 2 S + 1 N)	2 PLIES POLYESTER	1120kg
<b>TLT15R235C</b>	235mm	-	5 PLIES (2 P + 2 S + 1 N)	2 PLIES POLYESTER	1250kg

\* Please note the use of 'P', 'S' and 'N' in the *TREAD* column refers to the material of the plies. Please see code below:

- 'P' = Polyester
- 'S' = Steel
- 'N' = Nylon

*Please feel free to contact us for any further information you may require.*



## RIM AND TYRE SPECIFICATIONS:

<b>RIM + TYRE*</b>	<b>Tyre Size</b>	<b>Backspace</b>	<b>Frontspace</b>	<b>Offset</b>	<b>Single Rating</b>	<b>Double Rating</b>
<b>WRTFHT13P155</b>	155	80mm	80mm	0	515kg	487kg
<b>WRTFHT13P165</b>	165	85mm	77mm	0	670kg	650kg
<b>WRTFHT13P175</b>	175	90mm	80mm	0	730kg	690kg
<b>WRTF13G195</b>	195/50	105mm	95mm		900kg	825kg
<b>WRTF14P (+)</b>	185/	110mm	75mm	+14	850kg	800kg
<b>WRTF14P (0)</b>	185	100mm	100mm	0	850kg	800kg
<b>WRTF14P195</b>	195	120mm	85mm	+	950kg	900kg
<b>WRTLC14P</b>	185	100mm	100mm	0	850kg	800kg
<b>WRTLC14P195</b>	195	105mm	105mm	0	950kg	900kg
<b>WRTHQ14P</b>	185	110mm	75mm	+	850kg	800kg
<b>WRTHQ14P195</b>	195	115mm	80mm	+	950kg	900kg
<b>WRTH14P</b>	185	110mm	75mm	+	850kg	800kg
<b>WRTH14P195</b>	195	115mm	80mm	+	950kg	900kg
<b>WRTMF14G</b>	185	105mm	105mm	0	850kg	800kg
<b>WRTMF14G195</b>	195	105mm	105mm	0	950kg	900kg
<b>WRTHQ14G</b>	185	110mm	75mm	+	850kg	800kg
<b>WRTHQ14G195</b>	195	115mm	80mm	+	950kg	900kg
<b>WRTLC15P195</b>	195	105mm	105mm	0	950kg	900kg
<b>WRTLC15P225</b>	225	120mm	120mm	0	1000kg	900kg
<b>WRTLC15P235</b>	235	125mm	125mm	0	1250kg	1150kg
<b>WRTLC16P245</b>	245	130mm	130mm	0	1380kg	1260kg

\*Most wheels listed, excluding black rims as they are the same as white; same for 13" Galvanised rims as these also have the same specifications as the white ones listed.